

# simply radiators

## Aluminium Radiators – Data Sheet

Model	Section Height (mm)	Section Depth (mm)	Section Width (mm)	Tapping Centres (mm)	Water Content (Lt)	Output 60°C Δt (Watts)	Output 50°C Δt (Watts)
<b>Opera</b>							
R380	380	90	80	300	0.29	104	82
R480	480	90	80	400	0.35	129	102
R580	580	90	80	500	0.40	155	122
R680	680	90	80	600	0.46	180	141
R780	780	90	80	700	0.52	204	159
R880	880	90	80	800	0.60	225	176
<b>Graduate</b>							
RG430	428	98	80	350	0.33	133	105
RG580	578	98	80	500	0.41	176	138
RG680	678	98	80	600	0.46	203	159
RG780	778	98	80	700	0.51	229	179
RG880	878	98	80	800	0.56	253	198
<b>Highline</b>							
HA090	960	96	80	900	0.45	231	181
HA100	1060	96	80	1000	0.50	249	195
HA120	1260	96	80	1200	0.59	287	224
HA140	1460	96	80	1400	0.67	323	252
HA160	1660	96	80	1600	0.76	359	280
HA180	1860	96	80	1800	0.85	394	308
HA200	2060	96	80	2000	0.94	429	335

### Aluminium Radiators:

- All aluminium radiators are supplied in white as standard.
- Wall fixing brackets are included in the price for all aluminium radiators.
- Delivered pre-assembled up to 10 sections.
- A joining key is required for on-site assembly of radiators in excess of ten sections.
- Where required wall brackets, tapping bushes, plugs and air vents are supplied as standard and are free of charge.
- A comprehensive range of brackets and floor supports is available to give total flexibility.
- These aluminium radiators are designed for closed/indirect heating systems.
- All radiators have a maximum working pressure of 6 bar and are guaranteed against manufacturing defects for 10 years.
- Simply Radiators reserve the right to alter design, specifications and prices without prior notice.

simply radiators